

CSD SLIPSIL PLUG CHART FOR USE WITH STEEL, STAINLESS STEEL & CLASS 200 COPPERNICKEL PIPING

Service Pipe Run		Steel Pipe Sleeve to Use			SLIPSIL Part Numbers
IPS (in.)	OD (in.)	IPS (in.)	Schedule	Min. Length	
1/2	.840	2	40	120mm	53/20-22 SLIPSIL
3/4	1.050	2	40	120mm	53/26-28 SLIPSIL
1	1.315	2	40	120mm	53/33-34 SLIPSIL
1-1/4	1.66	3	40	160mm	78/42-44 SLIPSIL
1-1/2	1.90	3	40	160mm	78/48-50 SLIPSIL
2	2.375	4	40	160mm	102/60-62 SLIPSIL
2-1/2	2.875	4	40	160mm	102/74-75 SLIPSIL
3	3.50	5	40	160mm	128/88-90 SLIPSIL
3-1/2	4.00	6	40	160mm	154/102-104 SLIPSIL
4	4.50	6	40	160mm	154/114-116 SLIPSIL
5	5.583	8	40	160mm	203/141 SLIPSIL
6	6.625	8	40	160mm	203/168 SLIPSIL
Contact CSD	1-603-293-0100	E-Mail: info@csdsealingsystems.com			Rev 02/10